

3D print water jet cleaning station

PolyJet Waterjet



Tool Type: "Post processing/Cleaning"

Location: "Microfluidics Lab"

Supervisor	Tool Lead
David Bothman	
(805) 893-4125	
bothman@cnsi.ucsb.edu	

Description: "Waterjet Cleaner"

Manufacturer: "Stratasys "

About

This waterjet cleaner is mainly used to clean the support material off Objet prints. Parts should typically be scraped clean with the waterjet cleaner only used to remove material in hard to reach areas and micropores within the RGD 450.

Training

[Objet 30 Users Outline and SOP](#)

Detailed Specifications

- Water consumption: less than 12 L/min
 - 85-88 dB when operating
-

Safety Concerns

- Lid should remain latched and closed whenever the machine is on
 - Water should be shut off to the machine imminently after cleaning is finished to avoid accidental flooding
 - Cracked protective gloves should imminently be replaced
 - Do not operate water jet outside of sealed container
-

Reference Documentation

[objet_waterjet_installation_and_user_guide_-_english.pdf](#)

From:

<https://bpm-wiki.cnsi.ucsb.edu/> - NSF BioPACIFIC MIP Wiki

Permanent link:

https://bpm-wiki.cnsi.ucsb.edu/doku.php?id=3d_print_water_jet_cleaning_station&rev=1602177854

Last update: 2020/10/08 17:24

