FormLabs Form 2 SLA 3D Printer



Tool Type: "3D Printer"

Location: "Innovations Workshop"

Supervisor	Tool Lead
David Bothman	"WW Name"
(805) 893-4125	(###) ###-###
bothman@cnsi.ucsb.edu	"WW Email"

Description: "Stereolithographic 3D printer"

Manufacturer: "Formlabs"

About

The Form 2 Printers (Magnificent Ram and Electric Colt) are located in Fume Hood #2 in 2448 Elings Hall.

The Form 2 printers are liquid resin stereolithographic 3D printers capable of producing high resolution accurate models out of a variety of materials. Liquid resin printers use a bath of reactive resin which is precisely cured using specific wavelengths of light. This printer is particularly well suited for thin high aspect ratio features and models requiring great surface accuracy.

Based on the material and application, some prints will benefit from post process UV curing to strengthen and harden the finished part. See part curing documentation in UV FormCure reference documentation.

Last update: 2020/07/14 01:18

Detailed Specifications

Build Volume: 14.5 x 14.5 x 17.5 cm (L x W x H)

X,Y Accuracy: ~150 ish microns Layer Thickness: 25-300 microns

Printable Materials: Standard resin (clear or available colors), Durable resin, Flexible resin

Safety Concerns

The resin used in the Form 2 3D printers is considered hazardous. Gloves are to be warn when replacing or removing build plates, build tanks, and resin cartridges. Refer to SDS for disposal and health hazards.

Operating Procedures

- 1. Check resin cartridge and tank, make sure build material matches and is desired material.
- 2. If resin is not desired material, disconnect wiper at build tank, remove build plate by sliding towards front of fume hood. Remove cartridge, cap valve on bottom and close valve on top of cartridge. Replace build tank, wiper, and cartridge with desired material.
- 3. Launch Preform on Ultimaker computer
- 4. Import desired STL
- 5. Select "one click print" in the top left corner menu, change position, orientation, resolution and support as desired (note: that Preform will report on print ability of model, changing part rotation can affect print ability.
- 6. Select print (orange button) from top left menu
- 7. Select desired printer
- 8. Press button on Formlabs printer to start print

Reference Documentation

Form 2 design specifications

https://support.formlabs.com/s/article/Design-Specs?language=en US

flexible resin sds eu.pdf

formlabs clear-sds.pdf

durable resin sds eu.pdf

Training Documentation

form_2_teaching_handout.pdf

Safety Concerns

See SDS for desired resin material.

Training Outline

Key Points and Operating Checklist

From:

https://bpm-wiki.cnsi.ucsb.edu/ - NSF BioPACIFIC MIP Wiki

Permanent link:

https://bpm-wiki.cnsi.ucsb.edu/doku.php?id=form2&rev=1594689532

Last update: **2020/07/14 01:18**

